

JU16000V-22500 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic





Clamping Unit		JU16000 V Wide-Platen
Clamping Force	kN	16000
Mold Opening Stroke (Min/Max)	mm	2600/1850
Minimum Mold Height	mm	750
Maximum Mold Height	mm	1500
Maximum Daylight	mm	3350
Distance Between Tie-Bars (HXV)	mm	1915x1465
Platen Dimensions (HXV)	mm	2620x2175
Ejector Stroke	mm	450
Ejector Force	kN	450
Maximum Mold Weight*	t	40

JU16000V-22500 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic

Injection Unit		22500			
Screw & Barrel Designation		A	B	C	D
Screw Diameter	mm	140	150	160	170
Screw L/D Ratio	L/D	24	22.4	21	19.8
Injection Volume (theoretical)	cm ³	10467	12016	13672	15434
Injection Weight (PS)	g	9525	10935	12441	14045
Injection Rate (PS)	g/s	1352	1552	1766	1994
Injection Pressure	MPa	185	161	141	125
Injection Pressure (max)*	MPa	211	184	161	143
Plasticizing Rate (GPPS)	g/s	155	176	196	222
Plasticizing Rate (HDPE)	g/s	243	294	303	334
Screw Speed	rpm	85	85	85	85




JU16000V-22500 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic


Other		
Pump Motor Power	kW	205
Heater Power	kW	137
Machine Dimension (LxWxH)	m	12.93×4.03×4.40
Machine Weight	t	91
Hopper Capacity	kg	400
Oil Tank	l	1670

***NOTE:**

1. Injection Pressure (max) uses the machine's regeneration oil circuit to increase the injection pressure. This function will reduce injection control and repeatability. The standard "Injection Pressure" specification is the maximum injection pressure in a normal operating mode.
2. Moving platen max mold weight is 2/3 of total max mold weight.
3. Electric screw drive (screw rotate) is standard for injection units under 11500. For injection units 11500 and above electric screw drive is optional.
4. Machine dimensions and weights are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Cabletech Marketing service department for machine specific information.
5. Power requirements are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Cabletech Marketing service department for machine specific information.



Fixed Platen



Moving Platen



Title: JU V 1600W Fixed & Moving Platens Drawing

Machine Model: JU V 1600W

Machine Serial Number:

Machine Tonnage:

Sheet: 1 of 1

Drawn By: Harry

Date: 6/25/2024

Chkd By: LEON XIE

Date: 6/25/2024

NOT TO SCALE

Size: 11 X 17 "B"

Units: mm / [in]

Material:

Part:

Part:

Part:

Part:

Part:

PLEASE READ:

The designs on this drawing were validated using machine manufacturer's drawings and/or information supplied by Absolute or the customer. It is the responsibility of the customer to review and confirm that all dimensions are consistent with the application intended and in accordance with the facility requirements for space, part clearance, overhead clearance, or any other interference. By signing this document, the customer accepts full responsibility for this design and application.

Customer:

Customer Approval:

Authorized Signature

Notes: