

## JU10800V-6750

JUPITER 5 Series: Two-Platen Servo-Hydraulic



| Clamping Unit                   |    | JU10800V  |
|---------------------------------|----|-----------|
| Clamping Force                  | kN | 10800     |
| Mold Opening Stroke (Min/Max)   | mm | 1900/1200 |
| Minimum Mold Height             | mm | 500       |
| Maximum Mold Height             | mm | 1200      |
| Maximum Daylight                | mm | 2400      |
| Distance Between Tie-Bars (HXV) | mm | 1270x1100 |
| Platen Dimensions (HXV)         | mm | 1700x1660 |
| Ejector Stroke                  | mm | 350       |
| Ejector Force                   | kN | 230       |
| Maximum Mold Weight*            | t  | 16        |


# Specification



## JU10800V-6750

JUPITER 5 Series: Two-Platen Servo-Hydraulic

| Injection Unit                 |     | 6750  |       |       |
|--------------------------------|-----|-------|-------|-------|
| Screw & Barrel Designation     |     | A     | B     | C     |
| Screw Diameter                 | mm  | 90    | 100   | 110   |
| Screw L/D Ratio                | L/D | 24.4  | 22    | 20    |
| Injection Volume (theoretical) | cm3 | 2990  | 3691  | 4466  |
| Injection Weight (PS)          | g   | 2720  | 3359  | 4064  |
| Injection Rate (PS)            | g/s | 644   | 796   | 963   |
| Injection Pressure             | MPa | 193   | 156   | 129   |
| Injection Pressure (max)*      | MPa | 222   | 180   | 148   |
| Plasticizing Rate (GPPS)       | g/s | 103.4 | 127.1 | 150.2 |
| Plasticizing Rate (HDPE)       | g/s | 155.6 | 191   | 227.5 |
| Screw Speed                    | rpm | 170   | 170   | 170   |




## JU10800V-6750

JUPITER 5 Series: Two-Platen Servo-Hydraulic


| Other                     |    |                |
|---------------------------|----|----------------|
| Pump Motor Power          | kW | 105            |
| Heater Power              | kW | 71             |
| Machine Dimension (LxWxH) | m  | 9.37×3.28×3.07 |
| Machine Weight            | t  | 43             |
| Hopper Capacity           | kg | 100            |
| Oil Tank                  | l  | 590            |

**\*NOTE:**

1. Injection Pressure (max) uses the machine's regeneration oil circuit to increase the injection pressure. This function will reduce injection control and repeatability. The standard "Injection Pressure" specification is the maximum injection pressure in a normal operating mode.
2. Moving platen max mold weight is 2/3 of total max mold weight.
3. Electric screw drive (screw rotate) is standard for injection units under 11500. For injection units 11500 and above electric screw drive is optional.
4. Machine dimensions and weights are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Cabletech Marketing service department for machine specific information.
5. Power requirements are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Cabletech Marketing service department for machine specific information.



Fixed Platen



Moving Platen



Title: JUV 10800 Fixed & Moving Platens Drawing

Machine Model: JUV 10800  
Machine Serial Number:  
Machine Tonnage:


Sheet: 1 of 1  
Drawn By: Harry  
Date: 1/9/2024  
Chkd By: LEON XIE  
Date: 1/9/2024  
NOT TO SCALE  
Size: 11 X 17 "B"

| Revision | Date: | Drawing #: | Units: mm / [in] |
|----------|-------|------------|------------------|
| Rev #: 1 |       |            |                  |
| Rev #: 2 |       |            |                  |
| Rev #: 3 |       |            |                  |
| Rev #: 4 |       |            |                  |
| Rev #: 5 |       |            |                  |

PLEASE READ:  
The designs on this drawing were validated using machine manufacturer's drawings and/or information supplied by Absolute or the customer. It is the responsibility of the customer to review and confirm that all dimensions are consistent with the application intended and in accordance with the facility requirements for space, part clearance, overhead clearance, or any other interference. By signing this document, the customer accepts full responsibility for this design and application.

Customer: Customer Approval:  
Authorized Signature

Notes:



Title: JU V 10800-8950 Robot Mounting Drawing

Machine Model: JU V 10800-8950

Machine Serial Number:

Machine Tonnage:

Sheet: 1 of 1

Drawn By: Harry

Date: 4/9/2024

Chkd By: LEON XIE

Date: 4/9/2024

Revision

Date:

Drawing #: Robot Mounting

NOT TO SCALE

Size: 11 X 17 "B"

Rev #: 1

Units: mm / [in]

Rev #: 2

Material:

Rev #: 3

Part:

Rev #: 4

Part:

Rev #: 5

Part:

PLEASE READ:

The designs on this drawing were validated using machine manufacturer's drawings and/or information supplied by Absolute or the customer. It is the responsibility of the customer to review and confirm that all dimensions are consistent with the application intended and in accordance with the facility requirements for space, part clearance, overhead clearance, or any other interference. By signing this document, the customer accepts full responsibility for this design and application.

Customer:

Customer Approval:

Authorized Signature

Notes: