

JU10800V-6750 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic





Clamping Unit		JU10800 V Wide Platen
Clamping Force	kN	10800
Mold Opening Stroke (Min/Max)	mm	1950/1350
Minimum Mold Height	mm	600
Maximum Mold Height	mm	1200
Maximum Daylight	mm	2550
Distance Between Tie-Bars (HXV)	mm	1445x1195
Platen Dimensions (HXV)	mm	2000x1770
Ejector Stroke	mm	350
Ejector Force	kN	230
Maximum Mold Weight*	t	23

JU10800V-6750 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic

Injection Unit		6750		
Screw & Barrel Designation		A	B	C
Screw Diameter	mm	90	100	110
Screw L/D Ratio	L/D	24.4	22	20
Injection Volume (theoretical)	cm ³	2990	3691	4466
Injection Weight (PS)	g	2720	3359	4064
Injection Rate (PS)	g/s	809	999	1209
Injection Pressure	MPa	193	156	129
Injection Pressure (max)*	MPa	222	180	148
Plasticizing Rate (GPPS)	g/s	103.4	127.1	150.2
Plasticizing Rate (HDPE)	g/s	155.6	191	227.5
Screw Speed	rpm	170	170	170




JU10800V-6750 Wide Platen

JUPITER 5 Series: Two-Platen
Servo-Hydraulic


Other		
Pump Motor Power	kW	127
Heater Power	kW	71
Machine Dimension (LxWxH)	m	10.13x3.45x3.22
Machine Weight	t	50
Hopper Capacity	kg	50
Oil Tank	l	590

***NOTE:**

1. Injection Pressure (max) uses the machine's regeneration oil circuit to increase the injection pressure. This function will reduce injection control and repeatability. The standard "Injection Pressure" specification is the maximum injection pressure in a normal operating mode.
2. Moving platen max mold weight is 2/3 of total max mold weight.
3. Electric screw drive (screw rotate) is standard for injection units under 11500. For injection units 11500 and above electric screw drive is optional.
4. Machine dimensions and weights are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Cabletech Marketing service department for machine specific information.
5. Power requirements are based on the international standard configuration and are for reference only. Any options or country specific requirements will affect this. Contact Cabletech Marketing service department for machine specific information.



Fixed Platen



Moving Platen



Title: JU V 10800W Fixed & Moving Platens Drawing

Machine Model: JU V 10800W

Machine Serial Number:

Machine Tonnage:

Sheet: 1 of 1

Drawn By: Harry

Date: 6/25/2024

Chkd By: LEON XIE

Date: 6/25/2024

Revision Date: Drawing #:

Rev #: 1

Rev #: 2

Rev #: 3

Rev #: 4

Rev #: 5

NOT TO SCALE

Size: 11 X 17 "B"

Units: mm / [in]

Material:

Part:

Part:

Part:

Part:

PLEASE READ:

The designs on this drawing were validated using machine manufacturer's drawings and/or information supplied by Absolute or the customer. It is the responsibility of the customer to review and confirm that all dimensions are consistent with the application intended and in accordance with the facility requirements for space, part clearance, overhead clearance, or any other interference. By signing this document, the customer accepts full responsibility for this design and application.

Customer:

Customer Approval:

Authorized Signature

Notes: